

AIR BAG JACKS

PNEUMATIC PORTABLE JACKS



LIFTECH Air bag jacks are pneumatic powered, easy to use, quick to operate portable jacks with either two or three bellows.

- "H" models come with a long handle and 2 lockable positions for ease of manoeuvrability and storage.
- Jacks include a telescopic internal stabilizer.
- All jacks fitted with safety valves and stroke limiting device.
- Type-approved according to the European Standard EN1494.
- Manufactured in Europe.

TECHNICAL DATA

#	Working Load	Closed Height	Lift	Max. Height	Bellows	Working Pressure	Weight	Dia. of Airbag
LTABJ12	2,000 kg	118 mm	190 mm	308 mm	2	8-10 bar	14 kg	260 mm
LTABJ2	2,000 kg	132 mm	194 mm	326 mm	2	8-10 bar	14 kg	260 mm
LTABJ2H	2,000 kg	132 mm	194 mm	326 mm	2	8-10 bar	16 kg	260 mm
LTABJ3	2,000 kg	205 mm	285 mm	490 mm	3	8-10 bar	17 kg	260 mm
LTABJ3H	2,000 kg	205 mm	285 mm	490 mm	3	8-10 bar	19 kg	260 mm

LTABJ12



LTABJ2



LTABJ3



LTABJ2H



LTABJ3H

