VEHICLE SERVICE HOISTS BELLY LIFT



BELLY LIFT

- o Portable mid-rise frame lift.
- o Low clearance height suitable for low vehicles.
- o Portable control console.
- Wheel kit. Tow bar, and rubber riser blocks standard.
- Easy to relocate.
- o 3 Phase power.

TECHNICAL DATA

#	Working Load Limit	Closed Height	Raised Height	Overall Length	Overall Width	Platform Width	
LT1108	2,500 kg	110 mm	995 mm	1,966 mm	1,950 mm	460 mm	

LT1108



TRUCK RAMPS

- Handles slide out & wheels drop down for easy manoeuvrability and positioning of ramps.
 Handle slides away to safely remove a potential trip hazard.
- Flared lip protects the wheels from damage, and assists the vehicle from not driving off the top of the ramp.
- Ridges on ramp platform to ensure maximum tyre grip when loading and unloading.
- Rubber sheets attached to the base of the ramps to reduce slippage
- o LTR10 suitable for steer and dual wheels
- o LTR16 suitable for super single wheels.

TECHNICAL DATA

#	Working Load Limit	Platform Height	Overall Height	Platform Width	Overall Width	Platform Length	Overall Length	Package Size (cm)
LTR10	20,000 kg	185 mm	230 mm	245 mm	315 mm	500 mm	1,200 mm	130 x 34 x 26
LTR16	20,000 kg	185 mm	230 mm	400 mm	470 mm	500 mm	1,200 mm	130 x 48 x 26

LTR10

