

GARAGE JACKS

Liftech garage jacks are made to be strong, reliable and easy to use with a long service life. Standard, low height and high lift models are available.

- Universal joint release for trouble free operation.
- Frame designed for strength and durability.
- Wide wheel base for stability.
- Both the LT200TLPN and LT200TJN have turbo lift to load.

TECHNICAL DATA

#	Working Load Limit	Min. Height	Lift	Max. Height	Overall Length	Overall Width	Max. Frame Height	Net Weight	Pump
LT1300L	1,300 kg	80 mm	655mm	735 mm	970 mm	480 mm	160mm	38 kg	Manual
LT2000L	2,000 kg	80 mm	715mm	795 mm	970 mm	500 mm	220mm	49 kg	Manual
LT200TLPN	2,000 kg	68 mm	432mm	508 mm	710 mm	390 mm	145mm	36.5 kg	Manual
LT200TJN	2,000 kg	139 mm	331mm	470 mm	630 mm	340 mm	162mm	32 kg	Manual
LT400	4,000 kg	140 mm	460mm	600 mm	885 mm	400 mm	240mm	88 kg	Manual
LT1000	10,000 kg	150 mm	435mm	585 mm	805 mm	550 mm	260mm	118 kg	Manual

LT200TJN



LT200TLPN



HEAVY DUTY JACKS

LIFTECH Heavy Duty Air /Hydraulic Garage Jacks have been proven in Australian conditions for over 30 years. They are fitted with a mechanical quick lift device allowing the operator to raise the jack saddle up to the loading point very quickly with one movement of the jack handle. The light and compact design facilitates an easy and efficient operation even in a confined area. Rear wheels balance the total weight of the jack and enable the operator to move the jack in any direction easily by stepping on the foot plate provided on the rear end of the jack. Built in automatic safety valve prevents overloading.

TECHNICAL DATA

#	Working Load Limit	Min. Height	Lift	Max. Height	Overall Length	Overall Width	Max. Frame Height	Net Weight	Min. Operational Height
YM1000D	10,000 kg	160 mm	526 mm	686 mm	1,740 mm	528 mm	250 mm	150 kg	Manual
YMA1000D	10,000 kg	155 mm	525 mm	680 mm	1,740 mm	528 mm	250 mm	160 kg	Air /Manual
YMA1500LX	15,000 kg	175 mm	475 mm	650 mm	1,745 mm	530 mm	230 mm	240 kg	Air

YM1000D



YMA1500LX



YM1000D

