

RAMS & HAND PUMPS

- Internal heavy duty return spring provides consistent performance.
- Chrome plated piston inhibits rusting, scoring and corrosion.

TECHNICAL DATA

#	Description	Working Load Limit	Closed Height	Stroke	Extended Height	Coupling Size
601	Ram	10,000 kg	43 mm	11 mm	54 mm	1/4" NPT
678	Ram	4,000 kg	42 mm	16 mm	58 mm	1/4" NPT
680	Ram	2,000 kg	140 mm	76 mm	215 mm	1/4" NPT
685	Ram (Threaded)	10,000 kg	403 mm	257 mm	660 mm	1/4" NPT
688	Ram (Threaded)	10,000 kg	152 mm	49 mm	201 mm	3/8" NPT
SLS200	Ram	20,000 kg	51 mm	12 mm	63 mm	3/8" NPT
801-41	Ram (Slip on)	4,000 kg	227 mm	127 mm	354 mm	1/4" NPT
810-11	Spreader Ram	500 kg	16 mm	79 mm	95 mm	1/4" NPT
810-41	Ram (Slip on)	10,000 kg	369 mm	152 mm	522 mm	1/4" NPT
810-42	Hydraulic Hose	10,000 psi	Uses 810-P42 Coupling		Length 1,800 mm	1/4" NPT + 1/4" NPT
810-43	Hydraulic Hose	10,000 psi	With High Flow Couplings		Length 1,800 mm	1/4" NPT + 3/8" NPT
810-CA	Ram Coupling	N/A	N/A	N/A	N/A	1/4" NPT
810-P42	Hose Coupling	N/A	N/A	N/A	N/A	1/4" NPT

HAND PUMPS

- All metal construction.
- Internal overload valve prevents pump from being used beyond its rated capacity.
- External adjustable relief valve.
- Carrying handles for easy portability.

TECHNICAL DATA

#	Pressure Rating	Speed	Oil Capacity
804-40	4,000 psi / 276 bar	Single Speed	350 cc
810-40	10,000 psi / 700 bar	Single Speed	600 cc

