

TRUCK JACKS

Air hydraulic jacks designed for heavy vehicles such as trucks, buses and earthmoving equipment. Simple, reliable and easy to use. LIFTECH truck jacks have air powered ascent and descent, and are fitted with two descent valves to guarantee perfect holding and controlled speed under load. Ideal for workshops, mobile workshops, tyre repairers and bodyworkshops.

All LIFTECH Truck jacks come with extensions as standard.

- Designed for all types of heavy vehicles.
- Controlled by an air / hydraulic pump.
- Working air pressure 8-10 bar.
- Made in Europe from high quality materials.
- Conforms to the Machine Directive 98/37/CE, Type-approved according to the European Standard EN1494.

TECHNICAL DATA

#	Number of Stages	Working Load Limit Per Stage	Closed Height	Max. Height w/o Adaptors	Overall Length	Overall Width	Net Weight
LT215L	2	40,000 / 20,000 kg	150 mm	300 mm	700 mm	300 mm	39 kg
LT215N	2	40,000 / 20,000 kg	150 mm	300 mm	525 mm	300 mm	39 kg
LT217N	2	40,000 / 20,000 kg	170 mm	341 mm	525 mm	300 mm	51 kg
LT218N	2	60,000 / 30,000 kg	180 mm	340 mm	1,000 mm	350 mm	67 kg
LT312N	3	60,000 / 30,000 / 18,000 kg	120 mm	255 mm	660 mm	300 mm	50 kg
LT315L	3	60,000 / 30,000 / 18,000 kg	150 mm	335 mm	730 mm	300 mm	46 kg
LT318N	3	60,000 / 30,000 / 18,000 kg	180 mm	418 mm	1,000 mm	350 mm	69 kg
LT415N	4	70,000 / 43,000 / 23,000 / 13,000 kg	150 mm	400 mm	1,000 mm	350 mm	74 kg
LT418N	4	80,000 / 50,000 / 25,000 / 15,000 kg	180 mm	480 mm	1,000 mm	350 mm	76 kg
LT510N	5	55,000 / 40,000 / 28,000 / 18,000 / 10,000 kg	100 mm	260 mm	1,000 mm	350 mm	83 kg
LT215P	2	40,000 / 20,000 kg	150 mm	300 mm	500 mm	300 mm	35 kg

LT218N



LT215N



LT215P

