

INDUSTRIAL BOTTLE JACKS

TOE & LOCK RING JACKS



TOE JACKS

Masada Toe Jacks are Ideal jack for lifting loads with a low minimum jacking clearance. Uses an internal slide rail system for long life. Masada toe jacks are self retracting which eliminates manual lowering. The handle swivels 180° for operating in any direction. Applications include:

- House moving
- Machinery installation
- Applications at shipyards
- Bridge building
- Plant construction sites
- Forklift service.

TECHNICAL DATA

#	Working Load Limit Head / Toe	Closed Height Head / Toe	Toe Lift	Max. Height Head / Toe	Base Area	Weight
MHC-2RS	5,000 kg / 2,000 kg	243 mm / 19 mm	113 mm	350 mm / 132 mm	227 mm x 160 mm	12.5 kg
MHC-5RS	10,000 kg / 5,000 kg	290 mm / 22 mm	120 mm	410 mm / 142 mm	262 mm x 182 mm	18.5 kg
MHC-10RS	20,000 kg / 10,000 kg	325 mm / 28 mm	145 mm	470 mm / 173 mm	280 mm x 225 mm	35 kg

MHC-10RS



MHC-5RS



MHC-2RS



LOCK RING JACKS

These high quality bottle jacks use a lock ring located on the threaded ram of the jack to hold the job in a specified position. This type of jack is commonly used for fine adjustment of heavy machinery and heavy constructions, such as bridge building.

TECHNICAL DATA

#	Working Load Limit	Closed Height	Lift	Max. Height	Weight
MH-10LS	10,000 kg	300 mm	165 mm	545 mm	13 kg
MH-20L	20,000 kg	310 mm	160 mm	470 mm	15.3 kg

MH-20L

